

When Everything Comes Together


Plasson's comprehensive range of solutions for connecting PE pipe can be found in over 80 countries world-wide.

The combination of Plasson's high quality products and first class customer service make it a world leader in the production of plastic pipe fittings.





# **Metric x Universal**





# **Product Range:**

- mechanical
- pushfit
- electrofusion
- valves
- metering
- repair clamps
- threaded
- tools/accessories
- specialist ef tooling





### **Contact Us:**

Plasson UK Ltd Plasson House 27 Albert Drive **Burgess Hill** West Sussex **RH15 9TN** 


Tel: 01444 244446 Fax: 01444 258683 sales@plasson.co.uk

# **Plass4 Universal Coupler & Universal Elbow**


Plass4 is a universal pipe fitting which connects metric polyethylene to a wider range of pipe types: including imperial polyethylene (alkathene), copper (table X & Y), lead, galvanised steel, PVCu & poly-york.

Plass4 is easy to use with no specialist tools needed to complete the joint. The fitting is made from virgin polypropylene which makes it extremely strong and long-lasting. Plass4 fittings have a design life of 50 years, the same as our standard fittings. Due to its versatility, only a few fitting sizes are needed to cover all pipes from 15mm to 50mm.

#### 77017 Universal Coupler



Code	Size dxd1		E1	d	d1		l1	Н
77017251	25 x 15-22	54	64	25	15-22	58	80	165
77017252	25 x 20-27	54	71	25	20-27	58	85	170
77017253	25 x 27-35	54	83	25	27-35	58	90	180
77017500	32 x 20-27	64	71	32	20-27	67	85	180
77017323	32 x 27-35	64	83	32	27-35	67	90	195
77017504	50 x 35-50	96	121	50	35-50	93	125	270



Code	Size dxd1	Α	A1	d	d1	Е	E1	1	11
	25 x 15-22								
77057252	25 x 20-27	81	139	25	20-27	54	71	58	105
77057253	25 x 27-35	81	153	25	27-35	54	83	58	112

### Technical Specifications

reeninear specifications						
Maximum Pressure	PN16					
Operating Temperatures	Max 40°C / No minimum					
Body Material	Polypropylene, high grade copolymer					
Product Components	Nut Polypropylene Grip ring with integral stainless steel teeth NBR					
Standards	ISO 14236					

## **Key Features**

- Connects MDPE pipe to all metal pipe: Imperial & metric, copper, lead & steel.
- Connects plastic pipe, imperial & metric PE, UPVC & Poly-York.
- Couplers available to cover the O/D
- Elbows available to cover the O/D size
- Easy to use & no specialist tools needed.
- 50 year design life.